

**10 Gb/s, SFP+ LC Package, BIDI  
TX 1270/RX1330, TX 1330/RX1270 nm  
Single Mode, 10-60 km Distance**



**SFP+ Bi-Directional (BiDi) Transceivers**

**Description**

The bi-directional (BIDI) transceiver product is unique in that only one single fiber (single mode or multimode) is required to transmit and receive signals simultaneously. That means the total bandwidth capacity of an existing cable infrastructure can be doubled instantly. The typical design of a BIDI transceiver uses a 1270 nm LD to transmit and 1330 nm PD to receive, and vice versa for the matching one (1270 nm to receive and 1330 nm to transmit) at the other end to make a complete link.

OptixCom's SFP+ transceivers are compliant with SFP Multi-Source Agreement (MSA). The BIDI transceivers utilize advanced filter optics to separate the two wavelength with more than 40 dB of isolation. These transceivers operate at 10 Gb/s for 10-60 km transmission distance with single fibers. The products are RoHS compliant.



Lead-Free

**BD4-10000T2R3-ATXXK**  
**BD4-10000T3R2-ATXXK**  
**(XX = 10, 20, 40, 60)**



**Key Features**

- Single mode, 10 G/s data rate
- TX1270/RX1330 & TX1330/RX1270 nm pair
- > 6 dB power budget for 10 km
- > 12 dB power budget for 20 km
- > 16 dB power budget for 40 km
- > 20 dB power budget for 60 km
- Z-axis hot pluggable
- SFF-8472 MSA Compliant
- Single LC connector optical interface
- AC coupling LVPECL differential I/O logics
- -40-85 °C operating temperatures available
- Compliant with 10G FC Fiber Channel
- RoHS compliant



**Applications**

- ✓ 10G Fiber Channel,
- ✓ 10 Gigabit Ethernet
- ✓ High speed I/O for file server
- ✓ Data Communication for SAN and LAN
- ✓ Central offices routers and switches
- ✓ Computer cluster cross-connect

10 Gb/s, 2<sup>31</sup>-1 NRZ data eye pattern

TX

RX



**Ordering Information**

**Part Number:** BD4-10000T2R3-ATXXK

10 Gb/s, Single Mode, SFP+ BIDI Transceiver, TX 1270 nm and RX 1330 nm, **XX** km reach, 0 – 70 °C.

**Part Number:** BD4-10000T3R2-ATXXK

10 Gb/s, Single Mode, SFP+ BIDI Transceiver, TX 1330 nm and RX 1270 nm, **XX** km reach, 0 – 70 °C.

\* Add "-T" in the Part Number for -40-85 °C extended temperature range, i.e., BD4-10000T2R3-AT20K-T.

**Operating Conditions**

Parameter	Min.	Typical	Max.	Units
Operate Temperature	0	25	70	°C
- T Transceivers	-40	25	85	°C
Data Rate	9.95	---	11	Gb/s
Supply Voltage (3.3V)	3.13	3.3	3.47	V

**U.S.A. Office: Optix Communications, Inc.**

17901 Von Karman Avenue, Suite 600,  
Irvine, CA 92614

Tel: (949) 679-5712 Fax: (949) 420-2134

<http://www.OptixCom.com>

<http://www.OpticalTransceiver.com>

Email: [Support@OptixCom.com](mailto:Support@OptixCom.com)

**Germany Office: OptixCom GmbH**

Freiherr vom Stein Strasse 19, 60323  
Frankfurt am Main, Germany

Tel: +49 (0)69 7953-3646

### Absolute Maximum Ratings

Parameter	Symbol	Min.	Max.	Units
Storage Temperature	$T_{st}$	-40	85	°C
Supply Voltage @ 3.3V	$V_{CC}$	-0.5	3.6	V
Input Voltage	$V_{IN}$	-0.5	$V_{CC}$	V
Relative Humidity	$R.H.$	0	85	%

### General Transmitter Characteristics

Parameter	Symbol	Min.	Typical	Max.	Units
Differential Input Voltage <sup>1</sup>	$\Delta V_i$	0.2	---	1.2	V
Differential Input Impedance <sup>2</sup>	$Z$	---	100	---	ohm
Side Mode Suppression Ratio	SMSR	30	---	---	dB
Relative Intensity Noise	$RIN$	---	---	-128	dB/Hz
Rise/Fall Time (20% - 80%)	$T_r/T_f$	---	---	40	ps
TX Disable Voltage – High	$V_{DH}$	2.0	---	$V_{CC}$	V
TX Disable Voltage - Low	$V_{DL}$	0	---	0.8	V
TX Fault Output - High	$V_{FH}$	2.0	---	$V_{CC}$	V
TX Fault Output - Low	$V_{FL}$	0	---	0.8	V
TX Disable Assert Time	$T_{ass}$	---	---	10	μs
TX Disable Deassert Time	$T_{disass}$	---	---	1.0	ms
Time to Initialize	$T_{as}$	---	---	300	ms
TX Fault from Fault to Assertion	$T_{fault}$	---	---	100	μs
TX Disable Time to Start Reset	$T_{reset}$	10	---	---	μs

Notes:

1. Module is designed for AC LVPECL coupling. See the design guide for proper termination.
2. Single ended will be 50 ohm for each signal line.

**Class 1 Laser Product**  
Complies with  
**21 CFR 1040.10 and 1040.11**



### General Receiver Characteristics

Parameter	Symbol	Min.	Typical	Max.	Units
Differential Output Voltage <sup>1</sup>	$\Delta V_o$	0.3	---	0.7	V
Differential Input Impedance <sup>2</sup>	Z	---	100	---	Ohm
Optical Return Loss	OL	12	---	---	dB
Rise/Fall Time (20% - 80%)	$T_r/T_f$	---	---	40	ps
RX Signal Loss Output - High	$V_{RL+}$	2.0	---	$V_{CC}$	V
RX Signal Loss Output - Low	$V_{RL-}$	0	---	0.8	V
RX Signal Loss Assert Time	$T_{RL+}$	---	---	100	$\mu$ s
RX Signal Loss Deassert Time	$T_{RL-}$	---	---	100	$\mu$ s
Serial ID Clock Rate	$f_C$	---	---	100	kHz

Notes:

1. Module is designed for AC LVPECL coupling. See the design guide for proper termination.
2. Single ended will be 50 ohm for each signal line.

**Class 1 Laser Product**  
Complies with  
21 CFR 1040.10 and 1040.11



### Transmitter Electro-Optical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Units
Optical Output Power <sup>1</sup>	$P_o$	-2	---	+2	dBm
Optical Wavelength (BD4-1000T2R3-AT20K)	$\lambda_o$	1260	1270	1280	nm
Optical Wavelength (BD4-1000T3R2-AT20K)	$\lambda_o$	1320	1330	1340	nm
Extinction Ratio	$ET$	3.5	---	---	dB
Spectral Width (-20 dB)	$\Delta\lambda$	---	---	1	nm
TX Disable Asserted	$P_{OFF}$	---	---	-30	dBm

### Receiver Electro-Optical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Units
Operating Wavelength (BD4-1000T2R3-AT20K)	$\lambda_c$	1320	1330	1340	nm
Operating Wavelength (BD4-1000T3R2-AT20K)	$\lambda_c$	1260	1270	1280	nm
Receiver Overload	$P_{max}$	+0.5	---	---	dBm
Receiver Sensitivity <sup>2</sup>	$P_I$	---	---	-14	dBm
Receiver Sensitivity in OMA <sup>2</sup>	$P_I$	---	---	-12.5	dBm
RX Signal Loss – Asserted	$P_{RL+}$	---	---	-15	dBm
RX Signal Loss – Deasserted	$P_{RL-}$	-30	---	---	dBm

Notes:

1. Output of coupling optical power into 9/125  $\mu\text{m}$  SMF.
2. Test at 10 Gb/s,  $2^{31} - 1$  PRBS data pattern, and  $> 1 \times 10^{-12}$  of Bit-Error-Rate (BER).

**Class 1 Laser Product**  
Complies with  
**21 CFR 1040.10 and 1040.11**

